




### DIMENSIONS

### LAMPING

Nominal Diameter	Diffuser Diameter	Overall Height	Diffuser Height	Twin Tube Compact Fluorescent	Quad Tube Compact Fluorescent	Biaxial Fluorescent	Incandescent*	Special
24"	18"	8"	6"	(3)PL13	(2)Q26	N/A	(3)40W INC*	CONSULT FACTORY Use "SP" Prefix
30"	24"	9"	7"	(4)PL13	(3)Q26	N/A	(3)60W INC*	
36"	30"	11"	9"	(6)PL13	(4)Q26	(3)39BX	(4)60W INC*	
42"	36"	12 1/2"	10 1/2"	(6)PL13 (8)PL13	(4)Q26 (6)Q26	(4)39BX	(4)60W INC* (6)60W INC*	



\*Lower wattage incandescent lamps may be substituted.

### ORDERING KEY

**C** — 3150

MOUNTING	MODEL	DETAIL	NOM. DIAM.	MOUNTING	LAMPING	OPTIONS	VOLTAGE	OVERALL HEIGHT	FINISH
C-Ceiling Mount		0-Standard	24"	0-Standard	See Matrix	0-Standard	1-120V	0-Standard Height	PA-Painted (specify color - see finish brochure)
X-Special*		X-Special*	30"	X-Special*		SA-Satin Acrylic	2-277V		PB-Polished Brass
			36"			X-Special *	3-347V*		PC-Polished Nickel Chrome
			42"				X-Special*		SN-Satin Nickel Chrome
			X-Special*						SB-Satin Brass
									CB-Two-Tone Chrome & Brass
									X-Special *
									SEE FINISH BROCHURE FOR OPTIONAL FINISHES

\*Consult Factory Prior to Specification.

### SPECIFICATIONS

#### CONSTRUCTION

**Diffuser:** pure virgin acrylic  
**Hardware:** solid brass throughout  
**Internals:** white powdercoated C.R.S.

#### ELECTRICAL

**Incandescent Lamps:** medium base porcelain sockets  
**PL Lamps:** GX23 base sockets - HPF magnetic ballasts  
**Quad Lamps:** G24q base sockets - electronic ballast(s)  
**Biax Lamps:** 2G11 base sockets - electronic ballast(s)

#### CERTIFICATION

**All units:** UL listed dry location  
 Consult factory for damp location and Canadian labeling.

#### MOUNTING

**Standard:** designed for flat horizontal ceilings using an octagonal J-Box.

#### PHOTOMETRICS

Consult technical section for photometric reports.  
 Davis/Muller will gladly run photometric reports for your application at no cost or obligation. Ask your sales representative for details.

**MATCHED COMPANION FIXTURES AVAILABLE. CONSULT CATALOG.**



28 Beecher Street, Pawtucket, RI 02860  
 Toll Free Specifier Info. Line: (888) DAV-MULL (888-328-6855)  
 Toll Free Specifier Fax Line: (888) DAV-MUL6 (888-328-6856)

These fixture designs are copyright protected. Davis/Muller reserves the right to change fixture design and specifications in any way that will not significantly alter appearance or performance.

©1998, 2002, 2008 Davis/Muller Lighting



*signature series* C3150 *acrylic diffuser*